

MEDIA NOISE POST-PROCESSOR WITH VARYING THRESHOLD

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

0  
5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
10245  
10250  
10255  
10260

Al Cont.  
becomes increasingly difficult to distinguish adjacent data pulses, and the Viterbi techniques have been found to be very useful.

Sub A  
Unfortunately, significant errors still occur in data detection. For example, using EPR4 techniques, a bit error rate (BER) of about  $10^{-5}$  typically occurs. However it has been observed that if the signal to noise ratio in a system could be reduced by, for example, only 1 dB, the bit error rate can be improved to  $10^{-6}$ . This represents an order of magnitude improvement. Thus, even small improvements in the signal-to-noise ratio can result in large improvements in the bit error rate using EPR4 detection techniques. This is significant since presently the requirements exist for the provision of circuits that have a bit error rate less than  $10^{-7}$ , and it is expected that this requirement will continue to become more stringent.

66250-EEB-250  
In order to enhance the BER (bit error rate) performance, recently, post-processors have been incorporated with the Viterbi detector. An example of such post-processor is that shown in U.S. patent application serial number 09/229,945, filed January 13, 1999, entitled POST-PROCESSOR USING A NOISE WHITENED MATCHED FILTER FOR A MASS DATA STORAGE DEVICE, OR THE LIKE, by the inventors hereof, assigned to the assignee hereof, and incorporated herein by reference. However, in recent disk drives that have a high recording density, the media noise from the magnetic disk has become an important factor that is difficult to ignore.

25 The media noise arises primarily from written magnetic transitions, which typically have a zigzag transition geometry. The zigzag transition geometry produces position or pulse width uncertainties or "jitter" variations of read back signals. When media noise is dominant, it is difficult for such post-processors to improve performance, since the characteristic of media noise is quite different from white noise. The spectrum of the media noise

is not white, and is dependent on the data pattern written on the magnetic disk.

What is needed, therefore, is a post-processor that is effective for media noise in information storage and retrieval systems that use a magnetic data storage medium.

#### SUMMARY OF THE INVENTION

In light of the above, therefore, one of the advantages realized by the invention is that media noise or other transition jitter arising in an information storage and retrieval systems that uses a magnetic data storage medium can be controlled, using a post-processor in the read channel of the system.

Thus, according to a broad aspect of the invention, a post-processing method is presented for use in a sampled data read channel of a mass data storage device. The mass data storage device has a Viterbi detector that receives actual sampled partial response target data from a data medium of the mass data storage device. A recovered partial response target signal derived from the recovered data output signal and the sampled partial response target data is filtered to produce a filtered output signal, and a threshold circuit is provided to compare the filtered output signal against a predetermined threshold. When a predetermined error event pattern due to media noise or other transition jitter occurs in the recovered data output signal, a predetermined value is added to the filtered output signal, influencing the magnitude of the filtered output signal with respect to the threshold. The recovered data output signal is modified when the filtered output signal exceeds the threshold of the threshold circuit.

According to another broad aspect of the invention, a sampled data detection technique is presented for use in a mass data storage device to correct for media noise or other transition jitter. The method includes detecting an actual sampled partial response target from a transducer head of the mass data storage

device which has been equalized to a partial response level of at least  $EPR4$  in a Viterbi detector having a partial response detection level of at least  $EPR4$  to produce a recovered data output signal. The actual sampled partial response target signal is  
5 delayed for a time substantially equal to a time required by the Viterbi detector to generate the recovered data output signal from the actual sampled partial response target signal to produce a delayed actual sampled partial response target signal. The recovered data output signal is converted to a partial response  
10 level of the actual sampled data output signal to produce a converted recovered partial response target signal, and the converted recovered partial response target signal is subtracted from the delayed actual sampled partial response target signal to produce an error signal. The occurrence of a predetermined error event pattern in the recovered data output signal is determined to  
5 produce a filtered output signal, and a predetermined value is added to the filtered output signal when a predetermined error event pattern due to media noise or other transition jitter occurs in the recovered data output signal. The recovered data output  
10 signal is modified when the filtered output signal exceeds the threshold of the threshold circuit.

According to yet another broad aspect of the invention, a post-processor circuit is presented for use in a sampled data read channel of a mass data storage device of the type that uses a  
25 Viterbi detector that receives an actual sampled partial response target signal from a storage medium of the mass data storage device to produce a recovered data output signal. The circuit includes an error pattern detector to generate an error pattern event indicating signal if a predetermined error event pattern occurs in  
30 the sampled partial response target signal, and a circuit for generating an error signal based upon a difference between the recovered data output signal and a delayed the actual sampled

partial response target signal. A circuit is provided for adding a predetermined value to the error signal when a predetermined error event pattern due to media noise or other transition jitter occurs in the recovered data output signal, and a threshold circuit generates an error correction control signal if a magnitude of the error signal exceeds a predetermined threshold. An error correction circuit modifies the recovered data output signal when the error correction control signal and the error event pattern indicating occurrence signal are generated.

#### 10 BRIEF DESCRIPTION OF THE DRAWING

The invention is illustrated in the accompanying drawings, in which:

Fig. 1 is a diagram of a portion of a track of a magnetic storage medium, illustrating a "zigzag" jitter deviation of the data pattern recorded on the medium, illustrating one of the media noise situations addressed by the present invention.

Fig. 2 is a graph showing time vs. voltage showing variations in transition position due to position jitter resulting from the zigzag transition geometry shown in Fig. 1.

Fig. 3 is a graph showing time vs. voltage, illustrating typical variations in pulse width variations arising in the read back signals resulting from variations in position geometry shown in Fig. 1.

Fig. 4 is a block diagram of a circuit for use in a detecting and correcting jitter errors in a read back signal in an EEPR4 channel, in accordance with a preferred embodiment of the invention.

Fig. 5 is a block diagram of another circuit for use in a detecting and correcting jitter errors in a read back signal using an EPR4 channel using a preset value of +A or -A to be added when

ex =  $\pm 1$  at the output of the error detection filter, in accordance with another preferred embodiment of the invention.

Fig. 6 is a graph showing the ratio of peak jitter vs. bit error rate (BER) comparing the improvement realized in a circuit using a postprocessor with a circuit not using a postprocessor for correction of jitter noise.

Fig. 7 is a graph showing a ratio of peak jitter vs. bit error rate (BER), comparing the ideal to various coefficients in an EEP4 channel, in accordance with a preferred embodiment of the invention.

In the various figures of the drawings, like reference numerals are used to denote like or similar parts.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A diagram of a portion 10 of a track 12 of a magnetic storage medium 14, illustrating a "zigzag" jitter deviation of the data pattern recorded on the medium, illustrating one of the media noise situations addressed by the present invention, is shown in Fig. 1. It is, of course, desired that the magnetization pattern representing data or other information recorded onto the track 12 be located at a precise, predetermined location, denoted by the transverse line 16. However, due to many factors, including those described below, the magnetization pattern may have a zigzag transition configuration 18, which, for the reasons described below in detail, gives rise to media noise when the data is attempted to be read.

A time vs. voltage graph illustrating the variations in the position of the data transitions written onto the storage medium due to position jitter resulting from the zigzag transition geometry shown in Fig. 1 is shown in Fig. 2. As shown, the proper written transition position is that of the center location denoted by the axis line 20. The magnetization pattern on each side of the

axis 20 follows a generally Gaussian shaped pattern 22. However, due to the position jitter that occurs, the Gaussian waveforms that actually result are moved to the left and right of the center axis 20, as shown by the curves 24 and 26. Thus, a resulting voltage  
5 difference results between the peaks of the curves 24 and 26, which represents uncertainty in the position of the data read from the storage medium on which it is written. In the worst-case, this uncertainty may result in the data being miss-read.

In addition to position jitter, pulse width variations may  
10 arise in the read back signals from variations and position geometry of the recorded signals. This is shown in the graph of Fig. 3, in which the normal curve 22 which represents the data written to be centered on the axis 20, in fact, appears as if the data pattern were spread to produce the waveform 28. The wider data  
15 waveform pattern increases the probability of inter-symbol interference (ISI), which, also, can result in the data being miss-read.

Thus, the post-processor is a dedicated detector following the Viterbi detector to distinguish a few predetermined data patterns. Generally, the number of dominant error patterns of the Viterbi  
20 detector is very limited. The post-processor is designed to detect only these dominant error patterns. If the detection result of both detectors is different in the predetermined data patterns, the result of the post-processor may be selected so that the post-processor corrects the output data of the Viterbi detector. It can  
25 therefore be appreciated that the post-processor must have better performance in these pre-determined error patterns than the Viterbi detector.

In recent high recording density disk drives, it is difficult  
30 to ignore the media noise or other transition jitter from the magnetic disk. The media noise arises from written magnetic transitions which typically have a zigzag transition geometry, as

described above with reference to Fig. 1. The zigzag transition geometry typically arises from position jitter and the pulse width variation of read back signals, as described above with reference to Figs. 2 and 3.

When the media noise is dominant, it is difficult for such a post-processor, such as that as shown in the above referenced application, serial number 09/229,945 to improve performance, since the characteristics of the noise is different from white noise to which the post-process of said application serial number 09/229,945 is directed. The spectrum of media noise generally is not white, and is dependent at least in part on the data pattern written to the magnetic disk. (The errors due to the white noise depends on the data pattern, but the amount of the white noise itself does not depends on the data pattern; however, the amount of the media noise depends on the data pattern.) Thus, ideally, the media noise circuit herein described can be advantageously used to supplement the post-processor of said application serial number 09/229,945.

Referring now to a preferred embodiment of the media noise post-processing circuit and method of the invention, it should be noted that although the embodiment described below is an EEPR4 channel example with a Trellis 8/9 code (or TMTR 8/9 code), the technique of this invention can be applicable to various other PRML channels.

Table 1 shows the error event rate of error patterns of a Trellis 8/9 code EEPR4 Viterbi detector having 100% media noise. (Assuming that the media noise is position jitter noise, the sigma of the position jitter =  $0.1/T_d$ )

Table 1

	error pattern (in code)			Error event rate	
1	0 <u>1</u> 10	->	00 <u>0</u> 0	4.8E-5	60.9%
2	01 <u>1</u> 1	->	00 <u>0</u> 1	8.3E-6	10.5%



3	0111	->	0100	8.3E-6	10.5%
4	0111	->	0010	2.1E-6	2.7%
5	0100	->	0010	2.0E-6	2.5%
6	0010	->	0100	2.0E-6	2.5%
7	Others			7.9E-6	10.4%

The error patterns shown in the Table 1 are code patterns, with the code "1" arising when a magnetic transition occurs in the EEPR4 channel, and the code "0" arising when no transition occurs. In the Trellis 8/9 code, the maximum number of the consecutive "1" run length is limited to three. In general, the Viterbi detection error occurs in patterns in which the Euclidean distances between the correct path and the wrong path is small. However, when the media noise is dominant, the Viterbi detection error is controlled by both the Euclidean distance and the magnetic transition pattern.

It can be seen from Table 1 that the error patterns in rows 1-3 are the dominant error patterns of the Viterbi detector, accounting respectively for 60.9%, 10.5% and 10.5% event rates. The three dominant error patterns have the worst Euclidean distance in the EEPR4 channel and also includes the consecutive 2 or 3 transitions, which suggests that a large amount of media noise exists.

The error event rate of the opposite direction of the three dominant error patterns listed above are shown in Table 2

Table 2

	Error pattern (in code)			Error event rate
1'	0000	->	0110	1.3E-10
2'	0001	->	0111	2.7E-15
3'	0100	->	0111	2.7E-15

The error event rates of the error patterns of rows 1' to 3' are very small because these four bits patterns include a zero or one transition. (The reason why the "0000" pattern has small errors

is due to the media noise from data patterns which are adjacent to the "0000" pattern.) According to the present invention, a direction dependence of the error rate is utilized.

For an error pattern 1, the data of Table 3 applies:

5

Table 3

Error pattern (in code)			Error event rate
0110	->	0000	4.8E-5
0000	->	0110	1.3E-10

These error patterns are expressed in code. The error patterns at the read channel input are converted by the write flip-flop circuit. Thus, the error patterns at the read channel input are as shown in Table 4:

10

Table 4

From code	To	Channel input
0110	->	00100 or 11011
0000	->	00000 or 11111

The 0110 → 0000 error becomes either:

(1). 00100 → 00000 error or (2). 11011 → 11111 error

The 0000 → 0110 error becomes either

(3). 00000 → 00100 error or (4). 11111 → 11011 error

The patterns (1) and (2) are bad error rate patterns, and the patterns (3) and (4) are low error rate patterns. The error (1) 00100 → 00000 arises when a large negative noise comes to the error pattern sequence ("1" is erased). The error (3) 00000 → 00100 arises when a large positive noise comes to the error pattern sequence ("1" is generated).

The error rates of these examples are:

error (1): 00100 → 00000      2.4E-5

error (3): 00000 → 00100      6.5E-11

( error(1)+ error(3) =      2.4E-5 )

If some positive value (+A) is added to the error pattern sequence (1), the error rate will be remarkably reduced because the large negative noise that causes the error is compensated. If the same +A is added to the error pattern sequence (3), the error rate will increase, but the media noise of the error pattern (3) is very small, and the increase of the error rate is acceptable, if the value of +A is selected appropriately.

When the value of the +A is optimized, the error rate of (1) and (3) will be

10	error (1) 00100 → 00000	5E-8
	error (3) 00000 → 00100	5E-8
	(error(1)+ error(3) =	1E-7)

The error rate of (1) decreases about 3 orders of magnitude, the error rate of (3) increases about 3 orders of magnitude, and the total error rate of the two error patterns is improved about 2 orders of magnitude.

When the "00000" pattern is detected from the Viterbi detector output, The center bit of the "00000" pattern is the most suspicious. It has an error rate of 2.4E-5, but it is not known whether this bit is true or false. However, it can be assumed that the other four bits are true. Therefore, if the "00X00" pattern (X is 0 or 1) is detected from the output of the Viterbi detector, and the value of +A is added to the detector of the post-processor to compensate the media noise, we can expect the error rate improvement of error (1).

The error (2) 11011 → 11111 arises when a large positive noise exists in the error pattern sequence ("1" is generated). The error (4) 11111 → 11011 arises when a large negative noise exists in the error pattern sequence ("1" is erased). Thus, when the Viterbi detector outputs "11X11" pattern, in these error patterns, the performance can be improved by adding -A. The error rate of the

error patterns of rows 2 and 3 of Table 1 can be improved in the same way.

An example of a block diagram of a post-processor of the invention is shown in Fig. 4. The post-processor is similar to that shown in patent application serial number 09/229,945, and includes additional circuitry for media noise reduction. Thus, the post-processor in Fig. 4 is effective for both AWGN (white noise) and media noise.

More particularly, a block diagram circuit 30 is shown in Fig. 4, which represents is a data correction circuit in a sampled data read channel of a mass data storage device (not shown). The data detection and correction circuit 30, which is effective to detect and correct media noise errors, receives sampled data on the input line 32, which represents the equalized write current of the data storage medium. The sampled data provides an input to an EEP4 Viterbi detector 34, and to a delay circuit 36. The output from the Viterbi detector 34 represents the recovered write current, the respective sequential recovered write current samples being denoted by "k".

The recovered write current is applied to a filter 37, which includes a series of delay elements 40 - 48 that delay the respective samples of the recovered write current at the outputs from the Viterbi 34, each for a delay time D. The delay time, D, corresponds to the sample period of the sampled data on the input line 32, and, as known, corresponds to a delay operator, equal to  $e^{j\omega t}$ , where  $\omega$  is frequency, and  $t$  is delay time. The filter 37 may be an FIR filter, as shown. The inputs to the delay blocks 40, 41, 43, and 44 are multiplied by weighting factors 1, 2, -2, -1, respectively, and are summed by a summer circuit 50. The output from the summer 50 is a filtered output signal derived on the output line 51

The output from the summer circuit 50 is subtracted from the output of the delay circuit 36 to produce an error signal on line 52. The error signal provides an input to an error detection filter 54, which can detect the occurrence of the errors  $ex = \pm(1)$  and  $ex = \pm(1,-1)$ . The errors  $ex = \pm(1)$  and  $ex = \pm(1,-1)$  from the error detection filter 54 are provided as respective outputs on lines 56 and 58.

The signals on output line 56, which represents the error  $ex = \pm(1)$  are added to a predetermined value, and more particularly to the jitter error pattern  $\pm A$ , box 60, in adder 62. The absolute value of the summed the signal is compared to a threshold voltage of 2.50 volts in comparator 64. Concurrently, the polarity of the summed signal is the determined by a polarity checking circuit 66. The output from the comparator 64 is logically or'd with the output from the polarity checking circuit 66 to form the correction data, indicated by box 70. The correction is made to modify the output signal on line 49 in an output modification circuit 71 to produce an output signal on output line 73 when the threshold of the filtered signal, with the added jitter error pattern check, exceeds the threshold of the threshold detector 64.

The absolute value of the summed the signal on line 58, which represents the error  $ex = \pm(1,-1)$ , is compared to a threshold voltage of 2.25 volts in comparator 74. Concurrently, the polarity of the summed signal is the determined by a polarity checking circuit 76. The output from the comparator 74 is logically or'd with the output from the polarity checking circuit 76 to form the correction data, indicated by box 80. The corrected data is also applied to the output modification circuit 71 to produce the modified output on line 73.

The error patterns in rows 1, 2, and 3 of Table 1 are classified into  $ex = \pm(1)$  error pattern. Then in order to improve

the media noise performance only, we can remove the  $ex = \pm(1, -1)$  detection filter and the peripheral circuits. The error detection filters can be optimized for AWGN. When suspicious pre-determined patterns which may have the error due to the media noise are detected from the register (c6 to c-3) of the Viterbi detector output, the value of +A or -A is added to the output of the  $ex = \pm(1)$  detection filter.

The value of A depends on the ratio of the media noise and the AWGN, but may be preset in the programmable media noise compensation register. The error patterns to be detected from the Viterbi detector output are shown in the following table 5.

Table 5

Recovered Write Current $\hat{c}(k)$								Output
k	-3	-2	-1	0	1	2	3	
	X	0	0	X	0	0	X	Ajitter
	1	1	0	X	0	0	X	
	X	0	0	X	0	1	1	
	X	1	1	X	1	1	X	-Ajitter
	0	0	1	X	1	1	X	
	X	1	1	X	1	0	0	
Others								0

The output of the polarity check circuit 60 may be generated in accordance with the following table 6:

Table 6

Polarity Check				Correction	
Amplitude	Polarity	$\hat{c}(0)$	$\hat{c}(1)$	$\hat{c}(0)$	$\hat{c}(1)$
$ fexA(6)  > V_{thA}$	$FexA(6) > 0$	0	X	1	X
	$FexA(6) < 0$	1	X	0	X
$ FexB(6)  > V_{thA}$	$FexA(6) > 0$	0	1	1	0
	$FexA(6) < 0$	1	0	0	1

The three dominant error patterns in code shown in Table 1 become six error patterns in the read channel input.

The circuit 90 shown in Fig. 5 is an example of another application of this invention to the EPR4 channel. In this case, when the "0X0" and "1X1" patterns are detected from the Viterbi detector output, the pre-set value +A or -A is added to the  $ex = \pm (1)$  error detection filter.

The circuit 90 of Fig. 5 represents a postprocessor used in a 16/17 EPR 4  $ex = \pm(1)$  detector with media noise cancellation. The input to the system on input line 92 represents the samples output, for example, from the equalizer of a mass data storage device (not shown). The sampled signal on line 92 is connected to the inputs of an EPR 4 Viterbi detector 94 and a delay circuit 96. The output from the Viterbi detector 96 is connected to a series of delay circuits 100 -- 105. The outputs from the delay circuit 105 on line 110 represents the detected signal from the Viterbi detector, and its logical and with the input to the delay circuit 104 represents the "1X1" condition mentioned above. The logical or of the output signal on line 110 with the inputs to the delay circuit 104 represents the "0X0" condition also mentioned above.

The input lines to the delay circuits 100, 101, 102, and 103 are summed in a summer 108. The inputs to the delay circuit 102 and 103 are weighted by a -1 weighting factor, prior to being summed in the summer 108.

The output from the summer 108 is subtracted from the output of the delay circuit to 96 to produce an error signal on line 112. The signal on the line 112 is connected to a number of serially connected delay blocks 114 -- 120. The input to the delay circuit 114 is subtracted from the output of the delay circuit 120, the input to the delay circuit 115 is subtracted from the output of delay circuit 119, the input to delay circuit 116 is subtracted from the output of the delay circuit 118, and the inputs to the delay circuit 117 is subtracted from the output of the delay

circuit 117. The subtracted signals are weighted by respective weights 0.25, 0.5, 1, and 1, and are summed in a summer circuit 125. Depending upon the particular signal, the output from the summer is added to  $-A$ ,  $+A$ , or 0, for a signal "1X1", "0X0" or any others, respectively. The absolute value of the summed signal is compared to a threshold value of 2 in a threshold detector 128. The output from the threshold detector 128 is logically or'd with a signal representing the polarity of the summed signal to determine the correction value on output line 130. The value of  $A$  depends on the ratio of the media noise and the AWGN, but may be preset in the programmable media noise compensation register. The error patterns to be detected from the Viterbi detector output are shown in the following Table 7.

Table 7

Recovered Write Current $\hat{c}(k)$				Output
k	-1	0	1	
	0	X	0	Ajitter
	1	X	1	-Ajitter
Others				0

The polarity check correction values are straightforward, since the recovered write current is either 0 or 1, and may be established as shown in the following Table 8:

Table 8

Polarity check		Correction	
Amplitude	Polarity		
$ fexA  > VthA$	$FexA > 0$	0	1
	$FexA < 0$	1	0

The bit error rate simulation results are shown in fig.6 and Fig.7 for the EEPR4 channel and the EPR4 channel in 100% media noise.



It will be appreciated that the method of the invention can be used to improve the performance of the position jitter type noise induced by the media noise. The recent high density and high data rate disk drives suffer from position jitters of read back signals caused by the other sources. One such source is the write signal jitter. The write signals must be written to precisely the right position, but the actual write pulse signals have small random jitter elements induced by the system noise and various other interference producing causes.

Another jitter source is the write current asymmetry. The write current applied to the write magnetic head must be symmetrical (+ to - transition, and - to + transition) to write to the correct position of the data medium, but the rise time and the fall time of actual write current are not always symmetrical.

Another problem is a non-linear transition shift. Even if the write signals are written in the correct positions, the adjacent magnetization may interfere, and the correct positions of read back signals are shifted. This may cause the degradation of the error rate performance. The method of this invention is also effective for them.

Although the invention has been described and illustrated with a certain degree of particularity, it is understood that the present disclosure has been made only by way of example, and that numerous changes in the combination and arrangement of parts can be resorted to by those skilled in the art without departing from the spirit and scope of the invention, as hereinafter claimed.